#### Salisbury Pathways Committee

#### Sixty Fourth Meeting

Date and Time: Monday, April 11, 2022, at 5:30 p.m.

Location: Virtual via Zoom.

Present via Zoom: Natalia Smirnova, Kathy Trahan, Pat Hackett, Chris Williams, Gerry Stanton

#### Minutes:

Call to order -- 5:33 p.m.

- **1.** Approval of the minutes of February 14, 2022. Minutes were approved unanimously.
- 2. Status of the Connectivity Grant.

Application came back from DOT with 9 comments. Marc Mancini is working on answering the comments. More comments may come after the review from Bridge Maintenance and Soil and Foundation Department.

From: Marc S. Mancini <mmancini@slrconsulting.com>

**Sent:** Thursday, March 31, 2022 2:29 PM **To:** Curtis Rand <crand@salisburyct.us> **Subject:** CTDOT District 4 Comments

Hi Curtis,

CTDOT District 4 reviewed our Route 44 Sidewalk & Pedestrian Bridge plan very quickly. We will address and await potential comments from the CTDOT Bridge Maintenance group before re-submitting.

Please see comments attached.

Attached to these minutes are:

- 1. The comments from DOT.
- 2. The S.R. 44 Sidewalk FD Plan

Other items pertaining to the Connectivity grant:

- Property owners are all surveyed by the Town to get their approval for the sidewalk work. Everyone signed the agreement.
- DEEP is the longest holdup waiting on the comments from Bridge Maintenance and Soil and Foundation Department.
- Hopefully break ground by late summer.

- 3. Status of Library to Salmon Kill Road Sidewalk. Metcalf is ready to do the project. Matt Kiefer was asked to put the stakes for the sidewalk. Metcalf said mid-summer start. Pat Hackett is to communicate with Metcalf to find out when they are ready to start, then coordinate with Matt Kiefer.
- **4.** Committee Priorities revisit.

Natalia shared the minutes from September 15, 2014, where the following priorities were identified:

- 1. "Connector" connecting villages of Salisbury and Lakeville.
- 2. "Triangle with Horns" triangle that is comprised of Rt. 41 North, Cobble Road, Rt. 44 South with "horns" extending to Appalachian Trail parking lot on Rt. 41 and Lion's Head community on Rt. 44.
- 3. The Hotchkiss School
- 4. Belgo Road
- 5. Around the Lake
- 6. Lime Rock

Committee discussed how these priorities are achieved and amended for the current year.

- **1.** The **Connecto**r is progressing with the Connectivity grant. After that, we can do the connection from the Meadow to the Iron Bank. This will be the last stretch.
- **2.** Triangle with Horns: achieve this work in small sections:
  - 2.1. From the Ambulance on Rt. 41 North to Grove Street including the parking lot for the employees of White Hart connecting the Town Center to White Hart and parking.
  - 2.2. From Cobble Road down South to Grove Street by the Cemetery connecting Sarum Village to Town
  - 2.3. From Noble Horizons to the corner of Rt. 44 safety issue for residents.
  - 2.4. Cross Rt. 44 to the Rail Trail one crosswalk needed safety issue.

Other priorities must wait as the Committee works on those two top priorities.

**5.** Citizens comments. No citizens were present.

Meeting adjourned at 6:12 p.m.

Minutes respectfully submitted by Natalia V. Smirnova, Secretary, on April 18, 2022.

#### STATE OF CONNECTICUT DEPARTMENT OF TRANSPORTATION



subject: Town of Salisbury

Connectivity Grant

Route 44 from Lincoln City to Firehouse

date: March 29, 2022

Mr. Marc Mancini

to: Associate Transport

Associate Transportation Engineer

SLR

Email: mmancini@slrconsulting.com

from: Aron J. Steeves

Special Services Manager

District IV

**Bureau of Highway Operations** 

The following comments refer to the plan set entitled "CT S.R. 44 (Main St.) Sidewalk Improvements Salisbury, Connecticut CTDOT Project No. 0212-CCPI SLR Project No. 13039.00006 Final Design Plans" dated March 25, 2022, prepared by SLR.

No.	Comment	Inc.	Not Inc.
1.	<ul> <li>The proposed sidewalk runs adjacent to many trees/shrubs.</li> <li>Where excavation is within 3-5 times the DBH (diameter breast height) of any tree within the project, a licensed Arborist, hired by the contractor will be required to be on site to inspect and properly prune any roots damaged.</li> <li>Trees that had their root system damaged during excavation may require a fertilization and watering program.</li> <li>Any tree that sustains more than 33% root damage may be required to be removed at contractor's expense.</li> <li>At no time will excavated material be piled around the base of any tree or it's root system.</li> </ul>		
	A written report of any roots damaged within the project limits will be submitted to the District Landscape Designer.		
2.	It appears that the ramp on the northwest corner of Lincoln City Road should be a diagonal ramp. This ramp allows for the crossing of Lincoln City Road and Route 44.		
3	The horseshow shaped driveway at 227-229 Main Street appears to cross the property lines on both sides of the site. Please address.		
4	The pedestrian bridge has been sent to Bridge Maintenance for comments.		
5	Submit the pedestrian counter measure sheet to justify the RRFB at Brook Street and Route 44.		
6	See the marked up plans for the RRFB.		

TO: -2- **SUBJECT** FROM: Principal Engineer Project No.: DATE:

7	Have all the requirements for the Connectivity Grant been satisfied?	
8	Has the PAL agreement been written?	
9	More comments may come after the review from Bridge Maintenance and Soil and Foundation Department.	

Gina Greenalch

cc: Aron Steeves - Ron Ferris -

# CT S.R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS


# SALISBURY, CONNECTICUT

CTDOT PROJECT NO. 0121-CCP1 SLR PROJECT NO. 13039.00006


> FINAL DESIGN PLANS MARCH 25, 2022

#### **GENERAL NOTES**

- 1. TOPOGRAPHIC INFORMATION IS BASED UPON FIELD SURVEY CONDUCTED BY MILONE & MACBROOM, INC. ON JULY 16, 2019. STATE RIGHT OF WAY PER MAP REFERENCES FROM THE CONNECTICUT STATE HIGHWAY DEPARTMENT; ABUTTING STREET AND PROPERTY LINES DEPICTED PER GIS INFORMATION AND ARE APPROXIMATE IN NATURE.
- 2. NORTH ARROW AND BEARINGS ARE BASED UPON THE CONNECTICUT COORDINATE SYSTEM (NAD 1983). ELEVATIONS, CONTOURS AND BENCH MARK ARE BASED UPON (NAVD 1988)
- INFORMATION REGARDING THE LOCATION OF EXISTING UTILITIES HAS BEEN BASED UPON AVAILABLE INFORMATION AND MAY BE INCOMPLETE, AND WHERE SHOWN SHOULD BE CONSIDERED APPROXIMATE. THE LOCATION OF ALL EXISTING UTILITIES SHOULD BE CONFIRMED AT LEAST TWO FULL WORKING DAYS PRIOR TO BEGINNING CONSTRUCTION. CALL "CALL BEFORE YOU DIG", 811 OR WWW.CBYD.COM. ALL UTILITY LOCATIONS THAT DO NOT MATCH THE VERTICAL OR HORIZONTAL CONTROL SHOWN ON THE PLANS SHALL IMMEDIATELY BE BROUGHT TO THE ATTENTION OF THE ENGINEER FOR RESOLUTION.
- 4. MILONE & MACBROOM, INC. ACCEPTS NO RESPONSIBILITY FOR THE ACCURACY OF MAPS AND DATA WHICH HAVE BEEN SUPPLIED BY OTHERS.
- 5. ALL DIMENSIONS AND ELEVATIONS SHALL BE VERIFIED IN THE FIELD PRIOR TO CONSTRUCTION. ANY DISCREPANCIES SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER.
- 6. SEDIMENT AND EROSION CONTROL MEASURES AS DEPICTED ON THESE PLANS AND DESCRIBED WITHIN THE SEDIMENT AND EROSION CONTROL NARRATIVE SHALL BE IMPLEMENTED AND MAINTAINED UNTIL PERMANENT COVER AND STABILIZATION IS ESTABLISHED. ALL SEDIMENT AND EROSION CONTROL MEASURES SHALL CONFORM TO THE "GUIDELINES FOR SOIL EROSION AND SEDIMENT CONTROL, CONNECTICUT 2002". AND IN ALL CASES BEST MANAGEMENT PRACTICES SHALL PREVAIL
- 7. ALL DISTURBED AREAS SHALL RECEIVE A MINIMUM OF 4" TOPSOIL, AND BE SEEDED WITH GRASS UNLESS OTHERWISE NOTED.
- 8. ALL PROPOSED CONTOURS AND SPOT ELEVATIONS INDICATE FINISHED GRADE.
- ALL CONSTRUCTION MATERIALS AND METHODS SHALL CONFORM TO THE TOWN OF SALISBURY REQUIREMENTS AND TO THE
  APPLICABLE SECTIONS OF THE STATE OF CONNECTICUT DEPARTMENT OF TRANSPORTATION STANDARD SPECIFICATIONS FOR
  ROADS, BRIDGES, FACILITIES AND INCIDENTAL CONSTRUCTION, FORM 817 AND ADDENDUMS.
- 10. THE PLANS REQUIRE A CONTRACTOR'S WORKING KNOWLEDGE OF LOCAL, MUNICIPAL, WATER AUTHORITY, AND STATE CODES FOR UTILITY SYSTEMS. ANY CONFLICTS BETWEEN MATERIALS AND LOCATIONS SHOWN, AND LOCAL REQUIREMENTS SHALL BE BROUGHT TO THE ATTENTION OF THE ENGINEER PRIOR TO THE EXECUTION OF WORK. THE ENGINEER WILL NOT BE HELD LIABLE FOR COSTS INCURRED TO IMPLEMENT OR CORRECT WORK WHICH DOES NOT CONFORM TO LOCAL CODE.
- 11. ALL FUEL, OIL, PAINT, OR OTHER HAZARDOUS MATERIALS USED DURING CONSTRUCTION SHOULD BE STORED IN A SECONDARY
- 12. COMPLIANCE WITH THE PERMIT CONDITIONS IS THE RESPONSIBILITY OF BOTH THE CONTRACTOR AND THE PERMITTEE.
- 13. ALL SIGNS AND PAVEMENT MARKINGS INSTALLED ALONG THE STATE ROAD MUST CONFORM TO THE "MANUAL ON UNIFORM TRAFFIC CONTROL DEVICES," THE LATEST STATE OF CONNECTICUT CATALOG OF SIGNS AND STANDARD AS REVISED.
- 14. CONTRACTOR WILL BE REQUIRED TO OBTAIN A ROADWAY ENCROACHMENT PERMIT FROM CTDOT DISTRICT IV OFFICE PRIOR TO



#### **PROJECT SITE VICINITY MAP:**



#### PREPARED FOR:

CURTIS RAND - FIRST SELECTMAN TOWN OF SALISBURY 27 MAIN ST. P.O. BOX 548 SALISBURY, CT 06068

#### PREPARED BY:



#### LIST OF DRAWINGS

NO.	NAME	TITLE
01		TITLE SHEET
02	BOR-01	BORING LOGS
03	IND-01	INDEX PLAN
04	TYP-01	TYPICAL CROSS SECTIONS
05-07	EX-01 TO EX-03	EXISTING CONDITIONS & BASELINE PLANS
08-10	PLN-01 TO PLN-03	SIDEWALK PLANS
11-14	PRO-01 TO PRO-04	SIDEWALK PROFILE
05	STR-01	PEDESTRIAN BRIDGE - PLAN, ELEVATION AND SECTION
16-20	XSC-01 TO XSC-05	SIDEWALK CROSS SECTIONS
21	TCS-01	RRFB TRAFFIC CONTROL SIGNAL PLAN
22-24	MDS-01 TO MDS-05	MISCELLANEOUS DETAILS
		CTDOT STANDARD TRAFFIC DETAILS


CTDOT STANDARD HIGHWAY DETAILS

DESIGNED BY:



ANTHONY CIRIELLO JR., P.E.
CONN. PROFESSIONAL REG. NO. 20609
DATE:





	MII ON	JE S.	PROJECT:	MAIN STREE	T SIDEWALK	CONNECTION	١	BORING NO.:	MM-2	SHEE	T: 1 of 2		_
	MILON MACB	ROOM	LOCATION:	SALISBURY,	CONNECTIC	JT		CONTRACTO	R: GENERAL BORING	S, INC.			
	99 Realty [	Orive	PROJ. NO:	3039-06				FOREMAN: J.	WYANT				_
	Cheshire, CT (203) 271-		CLIENT:	TOWN OF SA	ALISBURY			INSPECTOR:	J. MONTAGNO				_
	(===, = : :		DATE:	JUNE 9, 2020	)	ī		GROUND SUF	RFACE ELEVATION: ±	718.0'			_
EQUIPM	ENT:	AUGER	CASING	SAMPLER	COREBRL.			UNDWATER D	EPTH (FT.)		TYPE OF RIG:		
TYPE		HSA	-	SS	-	DATE	TIME		WATER DEPTH		RIG MODEL:	MMER	_
SIZE ID		4 1/4	-	1 3/8	-	2020-06-09			±7.0'		RIG MODEL.		
HMR. W		-	-	140	-						DIEDRICH D-50		
HMR. FA	ALL (IN.)	-	-	30	-					1_		_	-
Depth (FT)	SAMPLE NUMBER	RECOVERY (IN)	BLOWS PER 6"	BURM				ION-DESCRIPT FENGINEERS	TION SYSTEM (ROCK)	DEPTH (FT.)	STRATUM DESCRIPTION	ELEV.	
			4	S-1: Loose, b	rown, fine to co	arse SAND, s	ome Silt, littl	e fine Gravel, tr	ace Roots.				•
1	S-1	2	2	1							TOPSOIL		
2			3	]	<u> </u>					2.0'		716.0	)
		_	7	S-2: Loose, b	rown, fine to co	oarse SAND, s	ome Silt, soi	me fine to coars	e Gravel,				
3	S-2	6	3	1									
4			3	1									
5				1		_					FILL		
			6 13	-1	dense, Top 7": Brown, fine to coarse SAND, some Silt, little fine Gravel, e.g., brick).								
6	S-3	18	7			orown, fine to coarse SAND, some Silt, some fine to coarse Gravel.							
7			5 17	S-4: Medium	dense Ton 8".	Brown fine to	coarse SAN	ID, some Silt, so	ome fine to	7.0' <b>G.W.T.</b> ▼ 711.0			)
8	S-4	12	14	coarse Grave		Brown, line to	coarse OAN	iD, some oni, se	onie iirie to		0.51		
°	5-4	12	7	Bottom 4": Gr	ay-brown, fine	to coarse GRA	VEL, little fi	ne to coarse Sa	nd, little Silt.	8.5' 709.			,
9			10	1									
10				S E. Von den	Ton 45: Dec	uum filma ta aas	ora CDAVE	'l some fine to	access Sand				
44	0.5	20	29 28	some Silt.	ise, rop 4 : bro	own, line to coa	arse GRAVE	L, some fine to	coarse Sand,				
11	S-5	20	23		•			arse Gravel, so					
12			17	DOLLOM 3": Gr	ay, iirie to coal	∍e GRAVEL, S	ome ine to	coarse SAND, s	ourie oiit.				
13				]									
				†									
14				]							GRAVEL WITH		
15			18	S-6: Dense, g	ıray-brown, fine	to coarse GR	AVEL, little t	fine to coarse Sa	and, trace Silt.		SAND & SILT		
16	S-6	5	28	]									
, ,			14 13	1									
17				]									
18				1									
19				]									
				1									
20			7						Sand, little Silt.				
21	S-7	10	<u>4</u> 5	Bottom 5": Gr	ay, SILT, some	e fine to coarse	Sand, som	e fine to coarse	Gravel.	21.0'		697.0	1.
22			7	]							SILT WITH		
				1							GRAVEL & SAND		
Remark	s:		•	•		PLASTIC		LASTIC	SAMPLE TYPE	•	PROPORTIO	NS	-
					N = 0 - 4 = VEI 4-10 = LOC		N = 0-2 = 2-4 =	SOFT	C = ROCK CORE S = SPLIT SPOON		trace = <10% little = 10% - 20%		
					10-30 = MI	EDIUM DENSE	4-8 =	MEDIUM	UP = UNDISTURBED PIS		some = 20% - 35%		
					30-50 = DE 50+ = VE	NSE RY DENSE	8 -15 : 15-30	= STIFF = VERY STIFF	UT = UNDISTURBED THII	NWALL	and = 35% - 50%		
					i		1		Ī.		i .		

#### <u>NOTES</u>

- 1. BORINGS BY SLR CONSULTING (MILONE & MACBROOM INC.) WERE PERFORMED BY GENERAL BORINGS, INC. ON 6/9/2020.
- 2. THE LOCATIONS OF THE BORINGS WERE DETERMINED BY TAPING/PACING FROM EXISTING SITE FEATURES. THESE LOCATIONS SHOULD BE CONSIDERED ACCURATE ONLY TO THE DEGREE IMPLIED BY THE METHOD USED.
- 3. THE LOCATIONS OF THE BORINGS ARE SHOWN ON SHEET EX-02.

AIN ST.) SIDEWALK IMPROVEMENTS

ST.)

ST.)


WHECTICUT

0.

MSM | MSM | AAC


**MARCH 25, 2022** 

13039.00006




#### CT S.R. 44 (MAIN ST.) SIDEWALK

STA. 10+10 TO 13+15 STA. 14+20 TO 17+75 STA. 21+25 TO 22+76




#### CT S.R. 44 (MAIN ST.) SIDEWALK


STA. 13+15 TO 14+20 STA. 17+75 TO 21+25 \* 6' SIDEWALK STA. 19+21 TO 20+30




CT S.R. 44 (MAIN ST.) SIDEWALK STA. 50+10 TO 50+75



CT S.R. 44 (MAIN ST.) SIDEWALK STA. 50+75 TO 52+15



CT S.R. 44 (MAIN ST.) SIDEWALK RESIDENTIAL DRIVEWAYS



CT S.R. 44 (MAIN ST.) SIDEWALK
COMMERCIAL DRIVEWAYS


#### LEGEND

- 2" BITUMINOUS CONCRETE SIDEWALK
- 2 8" PROCESS AGGREGATE BASE
- 3 4" TOPSOIL AND TURF ESTABLISHMENT
- 4 3" HMA S0.375
- (5) 4" HMA S0.375
- 6 12" PROCESS AGGREGATE BASE
- \* 2% MAX CROSS SLOPE

#### NOT


SEE BITUMINOUS CONCRETE SIDEWALK AND BITUMINOUS CONCRETE DRIVEWAY DETAILS ON STANDARD SHEET NO. HW-921-01








CROSS SECTIONS
(MAIN ST.) SIDEWALK IMPROVEMENTS


F 5 5 8							
MSM DESIGNED	MSM DRAWN	AAC CHECKED					
NTS SCALE							
MARCH 25, 2022							
13039.00006 PROJECT NO.							
DWG NO.	TYP-01						

















LTY DRIVE
ITE, CT 06410
1.1773
NSULTING.COM

DESCRIPTION DATE BY

R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS

MSM DESIGNED DRAWN AAC CHECKED


1"=20'
SCALE

MARCH 25, 2022
DATE

13039.00006
PROJECT NO.


PLN-02
DWG NO.

03



0' 10' 20'

STATE TO SEALTY DRIVE CHESHIRE, CT 06410 203.271.1773 SIRCONSULTING COM



EWALK PLAN S.R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS

MSM MSM AAC CHECKED


1"=20'
SCALE


MARCH 25, 2022
DATE


13039.00006
PROJECT NO.

PLN-03
DWG NO.

10








MSM MSM AAC
DESIGNED DRAWN CHECKED 1"=20' MARCH 25, 2022 **13039.0006** ROJECT NO. PRO-03

DESCRIPTION DATE	ВУ				
DESCRIPTION	DATE				
	DESCRIPTION				

MSM MSM AAC
DESIGNED DRAWN CHECKED MARCH 25, 2022 13039.00006



A193, CLASS 2, GRADE 8 (UNS DESIGNATION S 30400

SHALL BE 5/16" THICK STAINLESS STEEL AND CONFORM

TO ASTM A276, TYPE 304, ANNEALED. COST SHALL BE

(304)). THE NUTS SHALL BE PREVAILING-TORQUE

(UNS DESIGNATION S 030400 (304)). WASHERS

INCLUDED IN THE ITEM "PEDESTRIAN BRIDGE

SUPERSTRUCTURE (SITE NO. 1)"

REUSABLE-TYPE (WITH NYLON INSERT) LOCK NUTS AND CONFORM TO A194, GRADE 8, STRAIN HARDENED

#### GENERAL NOTES

- 1. <u>SPECIFICATIONS</u>: CONNECTICUT DEPARTMENT OF TRANSPORTATION FORM 818 (2020), AND SPECIAL PROVISIONS.
- 2. <u>DESIGN SPECIFICATIONS</u>: AASHTO LRFD DESIGN SPECIFICATIONS, 8<sup>TH</sup> EDITION, 2017, AS SUPPLEMENTED BY THE CONNECTICUT DEPARTMENT OF TRANSPORTATION BRIDGE DESIGN MANUAL (2003) WITH INTERIM REVISIONS UP TO AND INCLUDING 2011
- 3. MATERIAL STRENGTHS

CONCRETE: CLASS PCC 04460

f'c = 4,000 PSI

THE CONCRETE STRENGTH USED IN DESIGN (f'c) OF THE CONCRETE COMPONENTS IS NOTED ABOVE. THE COMPRESSIVE STRENGTH OF THE CONCRETE IN THE CONSTRUCTED COMPONENTS SHALL CONFORM TO THE REQUIREMENTS OF SECTION 6.01 - CONCRETE FOR STRUCTURES AND M.03 - PORTLAND CEMENT CONCRETE.

REINFORCEMENT: ASTM A615 GRADE 60

fy = 60,000 PSI

- 4. <u>LIVE LOAD:</u> 90 PSF PEDESTRIAN LOADING OR 6,000 LB VEHICULAR LOADING WHICHEVER GOVERNS (SEE SPECIAL PROVISION)
- 5. <u>DEAD LOAD</u>: ALL PEDESTRIAN BRIDGE COMPONENTS
- 6. FUTURE PAVING ALLOWANCE: NONE
- 7. EXISTING DIMENSIONS: DIMENSIONS AND ELEVATIONS OF THE EXISTING STRUCTURE SHOWN ON THESE PLANS ARE FOR GENERAL REFERENCE ONLY AND ARE NOT GUARANTEED. THE CONTRACTOR SHALL TAKE ALL FIELD MEASUREMENTS NECESSARY TO ASSURE PROPER FIT OF THE FINISH WORK AND SHALL ASSUME FULL RESPONSIBILITY FOR THEIR ACCURACY. WHEN SHOP DRAWINGS BASED ON FIELD MEASUREMENTS ARE SUBMITTED FOR APPROVAL, THE FIELD MEASUREMENTS SHALL ALSO BE SUBMITTED FOR REFERENCE BY THE REVIEWER.

#### CONCRETE NOTES

- 1. <u>REMAIN-IN-PLACE FORMS</u>: THE USE OF REMAIN-IN-PLACE FORMS ON THIS STRUCTURE IS NOT ALLOWED.
- 2. THE FOLLOWING PAY ITEMS AND CONCRETE CLASSES ARE REQUIRED FOR CAST-IN-PLACE BRIDGE COMPONENTS:

ITEM	BRIDGE COMPONENTS	PCC CLASS
ABUTMENT AND WALL CONCRETE	ABUTMENT STEM, BACKWALL, CHEEKWALLS	PCC04460

- 3. <u>EXPOSED EDGES</u>: EXPOSED EDGES OF CONCRETE SHALL BE BEVELED 1"x1" UNLESS DIMENSIONED OTHERWISE.
- 4. <u>CONCRETE COVER</u>: ALL REINFORCEMENT SHALL HAVE TWO INCHES COVER UNLESS DIMENSIONED OTHERWISE.
- 5. <u>REINFORCEMENT</u>: ALL REINFORCEMENT SHALL BE GALVANIZED AFTER FABRICATION UNLESS NOTED OTHERWISE. ALL REINFORCEMENT SHALL CONFORM TO THE REQUIREMENTS OF ASTM A767, CLASS 1, INCLUDING SUPPLEMENTAL REQUIREMENTS. THE COST OF FURNISHING AND PLACING THIS REINFORCEMENT SHALL BE INCLUDED IN THE ITEM "PEDESTRIAN BRIDGE" SUPERSTRUCTURE (SITE NO. 1)
- 6. <u>CONSTRUCTION JOINTS</u>: CONSTRUCTION JOINTS, OTHER THAN THOSE SHOWN ON THE PLANS, WILL NOT BE PERMITTED WITHOUT THE PRIOR APPROVAL OF THE ENGINEER.

#### PEDESTRIAN BRIDGE SUPERSTRUCTURE NOTES

- 1. PEDESTRIAN BRIDGE SUPERSTRUCTURE SHALL BE DESIGNED, FABRICATED, AND INSTALLED BY THE CONTRACTOR IN ACCORDANCE WITH TECHNICAL SPECIFICATIONS. SHOP DRAWINGS, DESIGN CALCULATIONS, AND ERECTION PLAN MUST BE SUBMITTED TO THE ENGINEER FOR APPROVAL PRIOR TO ORDERING MATERIAL OR CONSTRUCTING BRIDGE.
- 2. BRIDGE SEAT ELEVATIONS AND ANCHOR BOLT LOCATIONS SHALL BE DETERMINED BY THE BRIDGE MANUFACTURER. CONSTRUCTION OF THE ABUTMENTS SHALL NOT COMMENCE UNTIL SHOP DRAWINGS HAVE BEEN REVIEWED AND APPROVED BY THE ENGINEER.
- 3. ANCHOR BOLTS SHALL BE FULLY THREADED STAINLESS STEEL RODS AND CONFORM TO A193, CLASS 2, GRADE 8 (UNS DESIGNATION S 30400 (304)). THE NUTS SHALL BE PREVAILING-TORQUE REUSABLE-TYPE (WITH NYLON INSERT) LOCK NUTS AND CONFORM TO A194, GRADE 8, STRAIN HARDENED (UNS DESIGNATION S 030400 (304)). WASHERS SHALL BE ⅓16" THICK STAINLESS STEEL AND CONFORM TO ASTM A276, TYPE 304, ANNEALED. ANCHOR BOLTS SHALL BE PAID FOR UNDER ITEM "PEDESTRIAN BRIDGE SUPERSTRUCTURE (SITE NO.1)".
- 4. BEARINGS SHALL BE NEOPRENE ELASTOMERIC BEARING PADS DESIGNED IN ACCORDANCE WITH AASHTO LRFD BRIDGE DESIGN SPECIFICATIONS (5TH EDITION). BEARING PADS SHALL BE DESIGNED AND PAID FOR UNDER ITEM "PEDESTRIAN BRIDGE SUPERSTRUCTURE (SITE NO.1)".
- BRIDGE SHALL BE INSTALLED IN ACCORDANCE WITH MANUFACTURER'S RECOMMENDATIONS.
- 6. ALL MEMBERS OF VERTICAL TRUSSES (TOP AND BOTTOM CHORDS, VERTICAL AND DIAGONALS) AND LATERAL BRACING WITH CALCULATED TENSILE STRESSES SHALL BE DESIGNATED FRACTURE CRITICAL MEMBERS.
- 7. PREFABRICATED PEDESTRIAN BRIDGE SHALL BE PAINTED IN ACCORDANCE WITH THE TECHNICAL SPECIFICATIONS. BRIDGE MEMBERS SHALL BE FABRICATED FROM HIGH STRENGTH, LOW ALLOY STEEL CONFORMING TO THE REQUIREMENTS OF ASTM A M270, GRADE 50 AND IN ACCORDANCE WITH THE TECHNICAL SPECIFICATIONS. PLATE AND STRUCTURAL SHAPES SHALL BE Fy=50,000 PSI.
- 8. PAINT COLOR SHALL BE COORDINATED WITH THE TOWN PRIOR TO FABRICATION.
- 9. ¼" MINIMUM STEEL THICKNESS REQUIRED ON ALL STRUCTURAL MEMBERS.
- 10. WELDING DETAILS, PROCEDURES AND TESTING METHODS SHALL CONFORM TO THE ANSI/AWS D1.1 STRUCTURAL WELDING CODE, LATEST EDITION.
- 11. PROVIDE VERTICAL STEEL PICKETS, SUCH THAT THE MAXIMUM CLEAR OPENING IS 4". PROVIDE CLOSURE ANGLES AT TOP AND BOTTOM.
- 12. BRIDGE DECKING SHALL CONSIST OF IPE HARDWOOD.



CT S.R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS

CT S.R. 44 (MAIN ST.)

SALISBURY, CONNECTICUT

SEP SEP AAC CHECKED

AS SHOWN

CALE

MARCH 25, 2022


13039.00006

**06** 

STR-02


ABUTMENT NO. 1 PLAN

SCALE: 1" = 2'-0"




ABUTMENT NO. 1 ELEVATION

SCALE: 1" = 2'-0"




ABUTMENT NO. 1 PILE LAYOUT PLAN

SCALE: 1" = 2'-0"




ABUTMENT NO. 2 PLAN

SCALE: 1" = 2'-0"



ABUTMENT NO. 2 ELEVATION

SCALE: 1" = 2'-0"



ABUTMENT NO. 2 PILE LAYOUT PLAN

SCALE: 1" = 2'-0"

#### PILE NOTES

- 1. ALL PILES SHALL BE SET VERTICAL.
- 2. ESTIMATE OF PILES REQUIRED:

ABUTMENT NO. 1:


ABUTMENT NO. 2: fD(!D\*Ł', !=B `« `H=A 69F `D=@9`fl Ł'&' "- : H 5ddfcl "Ł

3. Hk 9 Ha 69F 'D=@9G'G< CI @8 '< 5J 9 '5 'A =B = AI A ', =B '« '6I HH 5B8 '5 'A =B = AI A '\* =B '« 'H-D''
THE PILES SHALL BE FROM SOUTHERN PINE OR DOUGLAS FIRM CONFORMING TO ASTM
D25 AND AWPA STANDARDS FOR CLASS 1 OR B PILES. THE PILES SHALL HAVE PRESSURE
TREATED PRESERVATIVE ACCEPTABLE FOR AWPA USE CATEGORY UC4C. PILES SHALL BE
DRIVEN WITH A HAMMER ENERGY OF 9,300 TO 15,000 FT-LBS. BASED ON THE
RELATIVELY LOW CAPACITY, THE CAPACITY IN THE FIELD CAN BE EVALUATED WITH THE
ENGINEERING NEWS RECORD FORMULA. THE PILES SHALL BE DRIVEN NO MORE THAN 12
BLOWS PER 1IN TO AVOID BROOMING OF THE PILES.

fD%|D'L', !=B'« 'H=A69F'D=@9'fl'L'&&"\*: H'5ddfcl "L

ULTIMATE PILE CAPACITY						
ABUTMENT NO. 1	13.1 TONS					
ABUTMENT NO. 2	13.1 TONS					





STRIAN BRIDGE - ABUTMENT LAYOUT . 44 (MAIN ST.) SIDEWALK IMPROVEMENTS

SEP DESIGNED DRAWN SEP CHECKED


AS SHOWN
SCALE


MARCH 25, 2022
DATE

13039.00006
PROJECT NO.


STR-03
DRAWING NO.

NO.









DEWALK CROSS SECTIONS
S.R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS
S.R. 44 (MAIN ST.)

MSM MSM AAC
DESIGNED DRAWN CHECKED


1"=5'
SCALE


MARCH 25, 2022
DATE

13039.00006
PROJECT NO.


XSC-01
DRAWING NO.

16












SIDE	CTS	CT S. SALIS					
MSM	MSM	AAC					
DESIGNED	DRAWN	CHECKED					
1"=5'							
SCALE							
MARCH 25, 2022							
13 PROJECT NO.	13039.00006 PROJECT NO.						
XSC-02 DRAWING NO.							
17							









|--|


1"=5'

MARCH 25, 2022

**13039.0006** DJECT NO.

XSC-03


**06** 



MSM MSM AAC
DESIGNED DRAWN CHECKED 1"=5' MARCH 25, 2022


**13039.00006** OJECT NO.

XSC-04



0' 2.5' 5' 0 1/2" 1"

SELECONSULTING.COM



CT S.R. 44 (MAIN ST.) SIDEWALK IMPROVEMENTS

CT S.R. 44 (MAIN ST.)

MSM MSM AAC
DESIGNED DRAWN CHECKED


1"=5'
SCALE


MARCH 25, 2022
DATE


13039.00006
PROJECT NO.

XSC-05
DRAWING NO.

20









SECTION AA

#### **GENERAL NOTES:**


- 1. SIDEWALK RAMPS SHALL HAVE A COARSE BROOM FINISH TRAVERSE TO THE SL 2. VERTICAL SURFACE DISCONTINUITIES AT JOINTS SHALL NOT EXCEED  $\frac{1}{4}$  INCH 3. REMOVAL OF EXISTING SIDEWALK FOR NEW RAMP INSTALLATIONS SHALL BE TO EXPANSION OR CONTRACTION JOINT.
- 4. THE RUNNING SLOPE OF THE CURB RAMP SHALL BE 8.3 PERCENT MAXIMUM BUT SHALL NOT REQUIRE THE RAMP LENGTH TO EXCEED 15 FEET.



#### SIDEWALK RAMP GRADE AT ROADWAY CROSS SLOPE OF 5% OR LESS



#### SIDEWALK RAMP GRADE AT ROADWAY CROSS SLOPE OF GREATER THAN 5%




- 1. TRANSITION SIDEWALK RAMP TO MATCH ROADWAY PROFILE AS GRADUALLY AS POSSIBLE.
  DO NOT EXCEED 3 % PER FOOT CROSS SLOPE
  RATE OF CHANGE WHEN TRANSITIONING TO
  ROADWAY PROFILE.
- 2. COMPLETE TRANSITION TO ROADWAY PROFILE BEHIND DETECTABLE WARNING SURFACE.

MSM MSM AAC NTS **MARCH 25, 2022** 13039.00006


**MDS-01** 

#### NOTES


- 1. ALL ITEMS SHOWN ARE INCLUDED IN THE COST OF "PAVEMENT REPAIR". SEE SPECIFICATIONS.
- 2. THIS DETAIL SHALL BE USED FOR PAVEMENT REPAIR FOR SIDEWALK INSTALLATIONS AS SHOWN ON PLANS.




# PERMANENT PAVEMENT FOR TRENCH THROUGH BITUMINOUS CONCRETE



# SEDIMENT FILTER FENCE





1. INSTALL BARRIER FOR A LENGTH EQUAL TO A DISTANCE OF 2' WIDER THAN THE DRIP LINE OF THE TREE.


DEEP ROOT BARRIER NOT TO SCALE

ВУ				
DATE				
DESCRIPTION				

MSM MSM AAC NTS

**MARCH 25, 2022** 

13039.00006 **MDS-02** 



SEDIMENT CONTROL SYSTEM AT CATCH BASIN NOT TO SCALE

MSM AAC MARCH 25, 2022

# ONLY STANDARD SHEETS MARKED WITH AN "V" ARE IN THIS PROJECT #

SHEET NO.	TITLE	APPROVA DATE
TR-1000_01	GENERAL CLAUSES (TEST PROCEDURES)	1/2014
TR-1001_01	TRENCHING & BACKFILLING, ELECTRICAL CONDUIT	4/2012
TR-1002_01	TRAFFIC CONTROL FOUNDATIONS	1/2014
TR-1010_01	CONCRETE HANDHOLE	4/2014
TR-1102_01	PEDESTALS, PEDESTRIAN SIGNALS	4/2012
TR-1105_01	TRAFFIC SIGNALS AND CABLE ASSIGNMENTS	8/2018
TR-1107_01	PEDESTRIAN PUSH BUTTON	8/2018
TR-1108_01	CONTROLLERS	5/2013
TR-1111_01	LOOP VEHICLE DETECTOR AND SAWCUT	4/2014
TR-1113_01	CONTROL CABLE	4/2014
TR-1114_01	BONDING & UTILITY POLE ATTACHMENT DETAILS, SIGN HANGER, "Y" CLAMP DETAILS	8/2018

TR-1210_02 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO TR-1210_03 SPECIAL DETAILS & TYPICAL PAVEMENT MARKINGS FOR TWO-WAY HIGHWAYS  OBSO TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	OVAL TE
TR-1208_02 METAL SIGN POSTS AND SIGN MOUNTING DETAILS  6/20  TR-1210_01 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO  TR-1210_02 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO  TR-1210_03 SPECIAL DETAILS & TYPICAL PAVEMENT MARKINGS FOR TWO-WAY HIGHWAYS  OBSO  TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	L8
TR-1210_01 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO TR-1210_02 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO TR-1210_03 SPECIAL DETAILS & TYPICAL PAVEMENT MARKINGS FOR TWO-WAY HIGHWAYS  OBSO TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	18
TR-1210_02 PAVEMENT MARKINGS (DURABLE MARKINGS) FOR DIVIDED HIGHWAYS  OBSO TR-1210_03 SPECIAL DETAILS & TYPICAL PAVEMENT MARKINGS FOR TWO-WAY HIGHWAYS  OBSO TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	L7
TR-1210_03 SPECIAL DETAILS & TYPICAL PAVEMENT MARKINGS FOR TWO-WAY HIGHWAYS  TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	LETE
TR-1210_04 PAVEMENT MARKING LINES AND SYMBOLS  TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS  4/20	LETE
TR-1210_05 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS 4/20	LETE
	18
TD 1210 OC DAVEMENT MADICINGS FOR DIVIDED LITCUMANC	L7
TR-1210_06 PAVEMENT MARKINGS FOR DIVIDED HIGHWAYS 8/20	18
TR-1210_07 PAVEMENT MARKINGS FOR EXIT RAMPS 4/20	L7
TR-1210_08 PAVEMENT MARKINGS FOR NON FREEWAYS 8/20	L8
TR-1210_09 PAVEMENT MARKINGS FOR BICYCLE LANES, PARKING STALLS, AND RR CROSSINGS 4/20	17
TR-1220_01 SIGNS FOR CONSTRUCTION AND PERMIT OPERATIONS 8/20	18
TR-1220_02 CONSTRUCTION SIGN SUPPORTS AND CHANNELIZING DEVICES 8/20	18

#### STANDARD SHEETS SHALL BE USED WITH STANDARD SPECIFICATIONS

			THE INFORMATION, INCLUDING ESTIMATED
			QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
4	4-2017	REMOVED TR-1210_01 TO TR-1210_03. ADDED TR-1210_04 TO TR-1210_09	INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE
3	4-2014	REMOVED TR-1111_02.	THE CONDITIONS OF ACTUAL QUANTITIES
2	1-2014	REMOVED TR-1103_01.	OF WORK WHICH WILL BE REQUIRED.
1	4-2012	RENUMBERED TR-1107_02 TO TR-1114_01. REMOVED TR-1116_01.	

REVISION DESCRIPTION

REV. DATE


Plotted Date: 8/16/2018


NOT TO SCALE

STATE OF CONNECTICUT **DEPARTMENT OF TRANSPORTATION** Filename: CTDOT\_TRAFFIC\_STD\_DGN.DGN Model: TR-01-STD\_INDEX

NAME/DATE/TIME: **CTDOT** STANDARD SHEET OFFICE OF ENGINEERING

**TRAFFIC** STANDARD SHEET INDEX






#### TRAFFIC CONTROL FOUNDATION PEDESTAL - TYPE I - PRECAST

NOTES:

PLACE NO. 6 CRUSHED STONE IN CENTER OPENING AFTER CONDUITS AND GROUND ROD HAVE BEEN INSTALLED.



#### TRAFFIC CONTROL FOUNDATION **CONTROLLER - TYPE IV - PRECAST**

EGEND AS SHOWN ON TRAFFIC CONTROL SIGNAL PLAN: PROPOSED CONTROLLER EXISTING CONTROLLER PROPOSED STEEL SPAN POLE EXISTING STEEL SPAN POLE

REVISION DESCRIPTION

1 4-2012 MINOR REVISIONS

REV. DATE

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES. & METRIC UNITS (mm). 1-2014 REMOVED SPAN POLE FOUNDATION DETAILS, REVISED TYPICAL THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED. CONCRETE SIDEWALK AT CONTROLLER FOUNDATION.

Plotted Date: 1/7/2014


IMENSIONS ARE IN ENGLISH ('.") ETRIC DIMENSIONS ARE ROUNDED OVER 1" TO NEAREST 5 mm UNDER 1" TO NEAREST 1 mm.

NOT TO SCALE



Model: TR-1002\_01


Filename: CTDOT\_TRAFFIC\_STD.DGN



# CTDOT STANDARD SHEET

TRAFFIC CONTROL FOUNDATIONS

TR-1002\_01




INSTALL PRECAST OR CAST IN PLACE CONCRETE SIDEWALK ON CABINET DOOR SIDE OF CONTROLLER FOUNDATION.


PITCH SIDEWALK  $\frac{1}{4}$ " PER FOOT (20 PER METER) AWAY FROM THE

CONTROLLER FOUNDATION.

REFER TO HIGHWAY STANDARD SHEET HW-921\_01 FOR SIDEWALK CONSTRUCTION.

#### TYPICAL CONCRETE SIDEWALK AT CONTROLLER FOUNDATION







#### TRAFFIC CONTROL FOUNDATION **CONTROLLER - TYPE IV - CAST IN PLACE**


NOTES:


INSTALL FOUNDATION ON 6" (150) OF COMPACTED GRAVEL IN ACCORDANCE WITH SECTION 2.14. LEVEL FOUNDATION WITH A PROJECTION OF 4" (100) ABOVE FINISHED GRADE. INSTALL COPPER GROUND ROD:  $\frac{5}{8}$ " x 10 (16 x 3000). PLACE NO. 6 CRUSHED STONE IN THE CENTER OPENINGS AFTER THE CONDUITS AND GROUND ROD HAVE BEEN INSTALLED. THE OPENINGS SHALL BE CAPPED WITH A 2" (50) GROUT LEVEL WITH THE TOP OF THE FOUNDATION AND NEATLY FINISHED. THE GROUT SHALL CONFORM WITH THE REQUIREMENTS OF ARTICLE M.3.01-12. CONCRETE: CLASS "A" CONFORMING TO ARTICLE M.03.01.

#4 REBAR 2" (50) MIN COVER AROUND ALL OPENINGS, 3-#4 REBARS IN EACH CORNER. CONDUITS SHALL NOT PROJECT MORE THAN 2" (50) ABOVE FOUNDATION.









SIGN # 31-0833 USE APPROPRIATE LEFT OR RIGHT ARROW



SIGN # 31-0835

FOR CROSSING WITH SIDE STREET GREEN

SURFACE MOUNTED


Plotted Date: 8/9/2018

PEDESTAL MOUNTED


**SPAN POLE/MAST ARM MOUNTED** 

**GENERAL NOTES:** 

3'-6" (1050) FROM FINISHED GRADE SUCH AS SIDEWALK TO CENTER OF PUSH BUTTON. PUSH BUTTON INSTALLATIONS SHALL CONFORM TO THE REQUIREMENTS OF THE AMERICANS WITH DISABILITIES ACT (ADA) STANDARDS FOR ACCESSIBLE DESIGN, CURRENT EDITION GOVERNS. 4'-4" (1300) PEDESTAL TO INCLUDE ALLOY CAP SECURED WITH STAINLESS STEEL SET SCREW.







ACCESSIBLE PEDESTRIAN SIGNAL AND DETECTOR

START CROSSING
Watch For Vehicles Watch For Vehicles Finish Crossing If Started TIME REMAINING To Finish Crossing DON'T CROSS TO CROSS

\*USE APPROPRIATE ARROW UNLESS OTHERWISE NOTED ON PLAN.

FOR NEW PUSHBUTTON HOUSING, USE 9" x 15" SIGN NO. 31-0856.

FOR EXISTING PUSHBUTTON HOUSING, WITH 9" x 12" SIZE, USE SIGN NO. 31-0845.

**EXAMPLE ALIGNMENTS** FOR EXCLUSIVE PEDESTRIAN PHASE

EGEND AS SHOWN ON TRAFFIC CONTROL SIGNAL PLAN: □ PEDESTRIAN PUSH BUTTON PEDESTRIAN PUSH BUTTON, PEDESTAL MOUNTED PEDESTRIAN PUSH BUTTON, POLE MOUNTED


REV. DATE

			THE INFORMATION, INCLUDING ESTIMATED
			QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED
			INVESTIGATIONS BY THE STATE AND IS
3	8-2018	UPDATED PEDESTRIAN SIGN LEGENDS AND NOTES.	IN NO WAY WARRANTED TO INDICATE THE CONDITIONS OF ACTUAL QUANTITIES
2	4-2014	ADDED PEDESTRIAN EXAMPLE ALIGNMENTS	OF WORK WHICH WILL BE REQUIRED.
1	4-2012	MINOR REVISIONS & LIDDATED SIGN #31-08/15	

REVISION DESCRIPTION

DIMENSIONS ARE IN ENGLISH ('.") & METRIC UNITS (mm). METRIC DIMENSIONS ARE ROUNDED:
- OVER 1" TO NEAREST 5 mm
- UNDER 1" TO NEAREST 1 mm.


NOT TO SCALE




Tracy of Fogulty APPROVED BY:	NAME/DATE/TIME:  Tracy L. Fogarty, P.E.  2018.08.16 12:13:35-04'00'  NAME/DATE/TIME:	CTDOT STANDARD SHEET
MFCR	Mark F. Carlino, P.E. 2018.08.21 07:46:57-04'00'	OFFICE OF ENGINEERING

PEDESTRIAN PUSH BUTTONS

TR-1107\_01






#### TYPICAL PLACEMENT OF OVERHEAD SIGNS ON SIGN SUPPORTS

NOTES:

- 1) FOR PLACEMENT OF CANTILEVER SIGN SUPPORT USE APPLICABLE PORTION OF ABOVE DETAIL.
- 2) BARRIER SYSTEMS MAY BE REQUIRED FOR BOTH SIDES OF SUPPORTS IN MEDIANS. 3) IMPACT PROTECTION SHALL BE PROVIDED FOR THE SIGN SUPPORTS LOCATED
- WITHIN CLEAR ZONE.
- 4) SIGN SUPPORT FOUNDATIONS SHALL BE LOCATED OUTSIDE OF BARRIER SYSTEMS DEFLECTION AREA.
- 5) ALL SIGNS ARE TO BE LEVEL, REGARDLESS OF CAMBER IN SUPPORT.



#### TYPICAL PLACEMENT OF SIDE MOUNTED SIGNS ON


#### STRUCTURAL STEEL BREAKAWAY SIGN SUPPORTS

NOTES:

REV. DATE


- 1) MIN. VERTICAL CLEARANCE ABOVE SIDEWALKS SHALL BE 7'.
- 2) WHERE GUIDE RAIL IS USED, THE OFFSET TO THE NEAR EDGE OF SIGN FACE SHALL BE AS SHOWN ELSEWHERE IN THE CONTRACT PLANS.
- 3) ON INTERSECTING ROADS AT RAMP TERMINI, THE OFFSET TO THE NEAR EDGE OF OF SIGN FACE SHALL BE 6'MIN. FROM POINT "E".
- 4) IF 30'-0" MIN. CANNOT BE MET, PLEASE CONTACT THE ENGINEER.

- FOR MAXIMUM EFFECTIVENESS, POSITION SIDE MOUNTED SIGNS ON STRUCTURAL STEEL BREAKAWAY SIGN SUPPORTS AS FOLLOWS:
- ON A TANGENT SECTION, POSITION THE SIGN SO THE VERTICAL AXIS IS PLUMB AND THE HORIZONTAL AXIS IS AT AN ANGLE OF 90° WITH THE TRAFFIC LANE WHICH THE SIGN SERVES. SIGNS LOCATED 30 FT OR MORE FROM THE EDGE OF THE ROAD SHALL BE TURNED APPROXIMATELY 3° TOWARD THE ROAD.





#### **DIAGRAM "A"**


ON A HORIZONTAL CURVE SECTION, POSITION THE SIGN SO THE VERTICAL AXIS IS PLUMB AND THE HORIZONTAL AXIS IS AT AN ANGLE OF 90° WITH A STRAIGHT LINE BETWEEN THE SIGN AND THE POINT AT WHICH THE SIGN SHALL BE READ.



#### SIGN ORIENTATION DETAILS FOR SIDE MOUNTED SIGNS ON STRUCTURAL STEEL BREAKAWAY SIGN SUPPORTS









#### RETROREFLECTIVE STRIP DETAIL

- RETROREFLECTIVE STRIPS WHICH ARE 48 IN LONG OR LESS SHALL BE ATTACHED USING 2 BOLTS AND RETROREFLECTIVE STRIPS OVER 48 IN LONG SHALL BE ATTACHED USING 3 BOLTS AS SHOWN ON THE DETAILS ABOVE.
- REFER TO STANDARD SHEET No. TR-1208\_02 "METAL SIGN POSTS
- AND SIGN MOUNTING DETAILS" FOR MOUNTING DETAILS. RETROREFLECTIVE STRIP COLOR SHALL MATCH THE BACKGROUND COLOR OF THE SIGN, EXCEPT THAT THE COLOR OF THE STRIP FOR "YIELD" AND "DO NOT ENTER" SIGNS SHALL BE RED.





# TYPICAL SIGN PLACEMENT DETAIL

NOTES:

ALL SIGNS AND SHIELDS ON DIRECTIONAL ASSEMBLIES SHALL ABUT VERTICALLY.

REFER TO STANDARD SHEET No. TR-1208\_02 "METAL SIGN POSTS AND SIGN MOUNTING DETAILS" FOR SIGN POSTS AND SIGN MOUNTING.

IF A RETFOREFLECTIVE STRIP IS USED ON SIGN SUPPORT, IT SHALL BE PLACED FOR THE FULL LENGTH OF THE SUPPORT FROM THE BOTTOM OF THE SIGN TO WITHIN 2 FT ABOVE THE EDGE OF THE ROADWAY. PARKING SIGNS TYPICALLY USE 45° MOUNTING BRACKET.

DIM."A" MIN SIGN HEIGHT	DIM."B" MIN LATERAL OFFSET (1)	DIM."C" MIN PLAQUE HEIGHT (1)	ASSEMBLY LOCATION
7' ②	6' 12' ③	5'	SIGNS ON FREEWAYS AND EXPRESSWAYS EXCEPT CHEVRON ALIGNMENT SIGNS, ONE-DIRECTION LARGE ARROW SIGNS, DO NOT ENTER SIGNS, AND WRONG WAY SIGNS
5'	2'	4'	• SIGNS IN RURAL AREAS • DO NOT ENTER AND WRONG WAY SIGNS ALONG EXIT RAMPS • DO NOT ENTER AND WRONG WAY SIGNS ON LIMITED ACCESS HIGHWAYS
5'	2'	N/A	CHEVRON ALIGNMENT SIGNS LOCATED ON FREEWAYS, EXPRESSWAYS, RAMPS, AND IN RURAL AREAS ONE-DIRECTION LARGE ARROW SIGNS LOCATED ON FREEWAYS, EXPRESSWAYS, RAMPS, AND IN RURAL AREAS
4'	6' 12' ③	N/A	INCIDENT MANAGEMENT SIGNS AND MILE POST MARKER ASSEMBLIES LOCATED ON FREEWAYS AND EXPRESSWAYS
4'	2'	4'	CENTRAL ISLANDS OF ROUNDABOUTS
7'	2' 4	6'	BUSINESS & RESIDENTIAL AREAS WHERE PARKING OR OTHER OBSTRUCTIONS LIMIT VISIBILITY
7'	2' 4	7'	SIDEWALKS 5

- OR AS DIRECTED BY THE ENGINEER
- 8 FT MINIMUM HEIGHT REQUIRED IF A SUPPLEMENTAL PLAQUE IS SUBMOUNTED BELOW THE MAJOR SIGN.
- 6 FT FROM EDGE OF SHOULDER, WHEN SHOULDER IS OVER 6 FT WIDE
- 12 FT FROM EDGE OF TRAVELWAY, WHEN SHOULDER IS LESS THAN 6 FT WIDE. A LATERAL OFFSET OF AT LEAST 1 FT FROM THE FACE OF THE CURB MAY BE USED WHERE SIDEWALK WIDTH
- IS LIMITED OR WHERE EXISTING UTILITY POLES ARE CLOSE TO THE CURB.
- (5) A CLEAR PATH OF NOT LESS THAN 4 FT SHALL BE PROVIDED IN SIDEWALK AREAS.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS NO WAY WARRANTED TO INDICATE 8-2018 | INCLUDED INCIDENT MANAGEMENT AND MILE MARKER SIGNS. THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED. 4-2017 MINOR REVISIONS 1 2-2011 MINOR REVISIONS

Plotted Date: 8/10/2018

REVISION DESCRIPTION

Filename: TR\_1208\_01\_1\_2018.dgn

NOT TO SCALE

STATE OF CONNECTICUT **DEPARTMENT OF TRANSPORTATION** 

Model: TR-1208\_01

NAME/DATE/TIME: Mark F. Makuch, P.E. 2018.08.17 09:06:06-04'00' PPROVED BY: NAME/DATE/TIME: Mark F. Carlino, P.E.


2018.08.21 07:48:06-04'00'


**CTDOT** STANDARD SHEET


OFFICE OF ENGINEERING


SIGN PLACEMENT AND


TR-1208\_01 RETROREFLECTIVE STRIP DETAILS













#### PORTABLE CONSTRUCTION SIGNS


NOTES FOR PORTABLE SIGN SUPPORTS:

- 1. SIGNS AND THEIR PORTABLE SUPPORTS SHALL CONFORM TO THE REQUIREMENTS OF NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH FOR CATEGORY 2 DEVICES AND THE LATEST EDITION OF THE MUTCD.
- 2. MOUNTING HEIGHT OF SIGNS SHALL BE A MINIMUM OF 12" AND A MAXIMUM OF 24". SIGNS SHALL BE MOUNTED HIGHER AS NEEDED TO MEET FIELD CONDITIONS OR AS DIRECTED BY THE ENGINEER.
- 3. THE ENGINEER RESERVES THE RIGHT TO REJECT ANY SUPPORT DEEMED UNSUITABLE FOR THE PURPOSE INTENDED.
- 4. PORTABLE SIGN SUPPORTS SHALL BE STABILIZED IN A MANNER THAT WILL NOT AFFECT THEIR COMPLIANCE WITH NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH FOR CATEGORY 2 DEVICES.
- 5. PORTABLE CONSTRUCTION SIGN SUPPORTS SHOULD NOT BE USED FOR DURATION OF MORE THAN 3 DAYS EXCEPT FOR R9-8 THROUGH R9-11a SERIES, R11 SERIES, W1-6 THROUGH W1-8 SERIES, M4-10, AND E5-1. SEE STANDARD SHEET TR-1220\_01 - "SIGNS FOR CONSTRUCTION AND PERMIT OPERATIONS" FOR SIGN DETAILS.
- \* FOR E5-1 (EXIT SIGNS) USE MIN 48".





TYPE I BARRICADE



5' MIN.


NOT TO SCALE

TYPE II BARRICADE

## CONSTRUCTION BARRICADES

#### NOTES:


- 1. CONSTRUCTION BARRICADES SHALL CONFORM TO THE REQUIREMENTS OF NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH AND THE LATEST EDITION OF THE MUTCD.
- 2. MARKINGS FOR BARRICADE RAILS SHALL BE ALTERNATE FLUORESCENT ORANGE AND WHITE STRIPES SLOPING DOWNWARD IN THE DIRECTION TRAFFIC IS TO PASS. 6" WIDE STRIPES SHALL BE USED.
- 3. THE ENTIRE AREA OF FLUORESCENT ORANGE AND WHITE STRIPES SHALL BE RETROREFLECTIVE SHEETING AS REQUIRED IN THE SPECIFICATIONS. THE SIDES OF BARRICADES FACING TRAFFIC SHALL HAVE RETROREFLECTIVE RAIL FACES.
- 4. THE ENGINEER RESERVES THE RIGHT TO REJECT ANY BARRICADE DEEMED UNSUITABLE FOR THE PURPOSE INTENDED.
- 5. CORNERS OF BARRICADE RAILS SHALL BE ROUNDED.
- 6. SIGNS MAY ONLY BE INSTALLED ON TYPE III BARRICADES AND SHALL BE PLACED SO AS TO COVER NO MORE THAN ONE BARRICADE RAIL.



#### **42" TRAFFIC CONE**

#### NOTES:

- 1. TRAFFIC CONES SHALL CONFORM TO THE REQUIREMENTS OF NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH FOR CATEGORY 1 DEVICES AND THE LATEST EDITION OF THE MUTCD.
- 2. IF RUBBER CONES ARE USED, THEY SHALL HAVE INTERIOR RIBS FOR RIGIDITY.
- 3. IF PLASTIC CONES ARE USED, THEY SHALL BE COLOR IMPREGNATED.
- 4. THE ENGINEER RESERVES THE RIGHT TO REJECT ANY CONE DEEMED UNSUITABLE FOR THE PURPOSE INTENDED.
- 5. THE ENTIRE AREA OF FLUORESCENT ORANGE AND WHITE STRIPES SHALL BE RETROREFLECTIVE SHEETING AS REQUIRED IN THE SPECIFICATIONS.
- 6. THE SECTIONS OF CONES NOT COVERED WITH RETROREFLECTIVE STRIPES SHALL BE ORANGE.



#### RURAL AREA

# PLACEMENT OF CONSTRUCTION SIGNS

TYPICAL LONG TERM INSTALLATION

#### NOTES:

SUPPORTS SHALL BE METAL SIGN POSTS AND HAVE BREAK-AWAY FEATURES.


REFER TO STANDARD SHEETS: TR-1208\_01 - "SIGN PLACEMENT AND RETROREFLECTIVE STRIP DETAILS." TR-1208\_02 - "METAL SIGN POSTS AND SIGN MOUNTING DETAILS."

# WHITE RETROREFLECTIVE STRIPE TYPE VI WHITE RETROREFLECTIVE STRIPE 28" MIN.

#### TRAFFIC CONE

#### NOTES:

- 1. TRAFFIC CONES SHALL CONFORM TO THE REQUIREMENTS OF NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH FOR CATEGORY 1 DEVICES AND THE LATEST EDITION OF THE MUTCD.
- 2. IF RUBBER CONES ARE USED, THEY SHALL HAVE INTERIOR RIBS FOR RIGIDITY.
- 3. IF PLASTIC CONES ARE USED, THEY SHALL BE COLOR IMPREGNATED.
- 4. THE ENGINEER RESERVES THE RIGHT TO REJECT ANY CONE DEEMED UNSUITABLE FOR THE PURPOSE INTENDED.
- 5. THE ENTIRE AREA OF WHITE STRIPES SHALL BE RETROREFLECTIVE SHEETING AS REQUIRED IN THE SPECIFICATIONS.
- 6. TRAFFIC CONES NOT USED AT NIGHT MAY UTILIZE TYPE III SHEETING.
- 7. THE SECTIONS OF CONES NOT COVERED WITH RETROREFLECTIVE STRIPES SHALL BE ORANGE.



#### TRAFFIC DRUM **FRONT VIEW**

#### NOTES:

- 1. TRAFFIC DRUM SHALL CONFORM TO THE REQUIREMENTS OF NCHRP REPORT 350 (TL-3) OR THE AASHTO MASH FOR CATEGORY 1 DEVICES AND THE LATEST EDITION OF THE MUTCD.
- 2. THE ENGINEER RESERVES THE RIGHT TO REJECT ANY DRUM DEEMED UNSUITABLE FOR THE PURPOSE INTENDED.
- 3. THE ENTIRE AREA OF FLUORESCENT ORANGE AND WHITE STRIPES SHALL BE RETROREFLECTIVE SHEETING AS REQUIRED IN THE SPECIFICATIONS.
- 4. THE SECTIONS OF DRUMS NOT COVERED WITH RETROREFLECTIVE STRIPES SHALL BE ORANGE.

THE INFORMATION, INCLUDING ESTIMATED QUANTITIES OF WORK, SHOWN ON THESE SHEETS IS BASED ON LIMITED INVESTIGATIONS BY THE STATE AND IS IN NO WAY WARRANTED TO INDICATE 8-2018 UPDATED SHEETING TYPE AND COLOR THE CONDITIONS OF ACTUAL QUANTITIES OF WORK WHICH WILL BE REQUIRED. 8-2015 UPDATED PER MUTCD AND FORM 816 JAN 2015 REVISION. 1 2-2011 MINOR REVISIONS REV. DATE REVISION DESCRIPTION Plotted Date: 8/10/2018

Filename: TR-1220\_02\_3\_2018.dgn

4' MIN.

TYPE III BARRICADE

STATE OF CONNECTICUT **DEPARTMENT OF TRANSPORTATION** 

Model: TR-1220\_02

DIRECTION OF

TRAFFIC

NAME/DATE/TIME: Mark F. Makuch, P.E. 2018.08.17 09:12:43-04'00' PPROVED BY: NAME/DATE/TIME: Mark F. Carlino, P.E. 2018.08.21 07:49:51-04'00

**CTDOT** STANDARD SHEET

OFFICE OF ENGINEERING

**URBAN AREA** 

**CONSTRUCTION SIGN SUPPORTS** AND CHANNELIZING DEVICES

TR-1220\_02

# \*ONLY STANDARD SHEETS MARKED WITH AN "\sqrt{" ARE IN THIS PROJECT #

### \*\*REVISED OR ADDED

<b>\</b> *	SHEET NO.	TITLE	APPROVAL DATE**
	HW-286_01	DRAINAGE TRENCH EXCAVATION	7-15-20
	HW-506 <sub>-</sub> 01	ENDWALLS, SLOPE PAVED INLETS AND OUTLETS	1-26-12
	HW-506_02	TYPE "D-G" & "L" ENDWALLS	7-13-12
	HW-506_03	ENDWALLS FOR PIPE - ARCH	9-18-09
	HW-586_01	CATCH BASIN AND DROP INLET TYPES "C" AND "C-L"	7-15-20
	HW-586_02	CATCH BASIN TOPS (TYPES "C" AND "C-L" ) FOR DOUBLE GRATE TYPE I	7-15-20
	HW-586_03	CATCH BASIN TOPS (TYPES "C" AND "C-L" ) FOR DOUBLE GRATE TYPE II	7-15-20
	HW-586_04	PRECAST CATCH BASIN AND ROUND STRUCTURE	7-15-20
	HW-586_05	PRECAST CATCH BASIN TYPES FOR DOUBLE GRATE TYPE I	7-15-20
	HW-586_06	PRECAST CATCH BASIN TYPES FOR DOUBLE GRATE TYPE II	7-15-20
	HW-586_07	CATCH BASIN TOPS TYPE "C" AND "C-L"	7-15-20
	HW-586_08	CATCH BASIN FRAMES AND GRATES	7-15-20
	HW-586_09	CATCH BASIN LOCK DOWN TOPS	7-15-20
	HW-586_10a	MANHOLE FRAME AND COVER	7-15-20
	HW-586_10b	MANHOLE FRAME AND GRATE	7-15-20
	HW-586_10c	REINFORCED PRECAST CONCRETE MANHOLE	7-15-20
	HW-586_10d	MANHOLE NON-PRECAST CONCRETE UNIT	7-15-20
	HW-686_01	C.C.M. PIPE INSTALLATION	7-15-20
	HW-686_02	PIPE ENDS	7-15-20
	HW-751_01	UNDERDRAINS AND UNDERDRAIN OUTLETS	7-12-12
	HW-803_01a	PAVED APRONS	6-07-17
	HW-803_01b	PAVED DITCHES AND PAVED CHANNELS	6-07-17
	HW-811_01	CONCRETE CURBING	6-07-17
	HW-813_01	GRANITE STONE TRANSITION CURBING	7-24-13
	HW-813_02	STONE CURBING	6-07-17
	HW-815_01	BITUMINOUS CONCRETE CURBING	6-07-17
	HW-821_01a	TRANSITION - 45" (1145) F-SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 1	1-26-12
	HW-821_01b	TRANSITION - 45" (1145) F-SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 2	10-18-10
	HW-821_01c	TRANSITION - 45" (1145) F-SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 3	1-26-12
	HW-821_02a		1-27-20
	HW-821_02b		1-27-20
	HW-821_03a	TRANSITION - 32" (813) JERSEY SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 1	1-26-12

<b>\</b> *	SHEET NO.	TITLE	APPROVAL DATE**
	HW-821_03b	TRANSITION - 32" (813) JERSEY SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 2	10-18-10
	HW-821_03c	TRANSITION - 32" (813) JERSEY SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 3	10-18-10
	HW-821_03d	TRANSITION - 32" (813) JERSEY SHAPE TO 45" (1145) VERTICAL SHAPE SHEET 4	10-18-10
	HW-821_03e	TRANSITION - 32" (813) JERSEY SHAPE TO 45" (1145) F-SHAPE	7-24-13
	HW-821_04a	MERRITT PARKWAY NARROW MEDIAN BARRIER	6-09-11
	HW-821_04b	MERRITT PARKWAY - 2'(610) WIDE MEDIAN BARRIER AND ROADSIDE BARRIER	7-24-13
	HW-821_05a	TRANSITION - 45" (1145) F-SHAPE TO 54" (1372) VERTICAL SHAPE SHEET 1	1-26-12
	HW-821_05b	TRANSITION - 45" (1145) F-SHAPE TO 54" (1372) VERTICAL SHAPE SHEET 2	1-26-12
	HW-821_06	54" (1372) VERTICAL SHAPE BARRIER	2-06-12
	HW-821_07	MISCELLANOUS DETAILS FOR BARRIER TRANSITIONS	7-12-12
	HW-821_08a	F-SHAPE CONC. BARRIER CURB (21"x45") TRANSITION FOR THRIE-BEAM	1-09-20
	HW-821_08b	F-SHAPE CONC. BARRIER CURB (21"x45") TRANSITION FOR THRIE-BEAM - REINF.	1-09-20
	HW-821_09a	SINGLE SLOPE CONC. BARRIER CURB (20"x42") TRANS. FOR THRIE-BEAM	1-09-20
	HW-821_09b	SINGLE SLOPE CONC. BARRIER CURB (20"x42") TRANS. FOR THRIE-BEAM - REINF.	1-09-20
	HW-821_10a	VERTICAL FACE CONC. (21"x54") TRANSITION FOR THRIE-BEAM	1-09-20
	HW-821_10b	VERTICAL FACE CONC. (21"x54") TRANSITION FOR THRIE-BEAM - REINF.	1-09-20
	HW-821_11a	42" SINGLE SLOPE PRECAST CONCRETE BARRIER CURB -SHEET 1	1-27-20
	HW-821_11b	42" SINGLE SLOPE PRECAST CONCRETE BARRIER CURB -SHEET 2	1-27-20
	HW-822_01	TEMPORARY PRECAST CONCRETE BARRIER CURB	7-24-13
	HW-905_01	STONE WALL FENCE	1-25-19
	HW-906_01	WIRE FENCE	1-25-19
	HW-910_01	W-BEAM METAL BEAM RAIL HARDWARE	6-09-11
	HW-910_02	METAL BEAM RAIL (TYPE R-B 350) GUIDERAIL	6-09-11
	HW-910_03	METAL BEAM RAIL (TYPE MD-B 350) GUIDERAIL	6-09-11
	HW-910_04	METAL BEAM RAIL (TYPE R-B 350) SYSTEMS 5, 5A, & 6	6-09-11
	HW-910_05	METAL BEAM RAIL R-B 350 SPAN TYPE I, II, III SECTIONS	7-24-13
	HW-910_06	R-B 350 BRIDGE ATTACHMENT SAFETY SHAPE PARAPET	6-09-11
	HW-910_07	R-B 350 BRIDGE ATTACHMENT VERTICAL SHAPE PARAPET	1-25-19
	HW-910_08	R-B 350 BRIDGE ATTACHMENT TRAILING END	6-09-11
	HW-910_09a	MISCELLANEOUS GUIDERAIL TRANSITIONS SHEET 1	1-26-12
	HW-910_09b	MISCELLANEOUS GUIDERAIL TRANSITIONS SHEET 2	7-25-12
	HW-910_10	METAL BEAM RAIL 8" (203) X 6" (152) BOX BEAM	7-24-13
	HW-910_11	CURVED GUIDERAIL TREATMENT DETAIL	7-25-12

ATURE BLOCK:

OFFICE OF ENGINEERING
2800 BERLIN TURNPIKE
NEWINGTON, CT 06111

NOT TO SCALE

STATE OF CONNECTICUT

DEPARTMENT

OF

TRANSPORTATION

# \*ONLY STANDARD SHEETS MARKED WITH AN "√" ARE IN THIS PROJECT # \*\*REVISED OR ADDED

SHEET NO.	TITLE	APPROVAL DATE**	SHEET NO.	TITLE	APPROVAL DATE**
HW-910_12a	MERRITT PARKWAY GUIDERAIL LEADING END ATTACHMENTS AND SYSTEMS 2&3	7-24-13	HW-921_01	DRIVEWAY RAMPS AND SIDEWALKS	6-07-17
HW-910_12b	MERRITT PARKWAY GUIDERAIL HARDWARE DETAILS	7-24-13	HW-949_01a	LANDSCAPE PLANTING	6-15-19
HW-910_12c	MERRITT PARKWAY GUIDERAIL TRAILING END ATTACHMENTS	7-24-13	HW-949_01b	TREE STAKING	6-15-19
HW-910_12d	MERRITT PARKWAY MEDIAN GUIDERAIL AND END ANCHOR	6-09-11	HW-1800_01	GRADING PLAN FOR IMPACT ATTENUATION SYSTEMS (FLARED AND TANGENTIAL)	1-25-19
HW-910_13a	THRIE-BEAM METAL BEAM RAIL HARDWARE	7-24-13	HW-1800 02	GRADING PLAN FOR IMPACT ATTENUATION SYSTEMS (MEDIAN/GORE)	1-25-20
HW-910_13b	THRIE-BEAM TRANSITIONS	7-24-13			
HW-910_14a	THRIE-BEAM 350 BRIDGE ATTACHMENT	6-09-11			
HW-910_14b	THRIE-BEAM 350 GUIDERAIL TRANSITION TO R-B 350 GUIDERAIL	6-09-11			
HW-910_15	MD-B 350 MEDIAN BARRIER SAFETY SHAPE ATTACHMENT TYPE I	6-09-11			
HW-910_16	MD-B 350 MEDIAN BARRIER SAFETY SHAPE ATTACHMENT TYPE II	6-09-11			
HW-910_17	R-B TERMINAL SECTION	7-24-13			
HW-910_18	METAL BEAM RAIL (TYPE MD-I) GUIDERAIL	10-18-10			
HW-910_19a	METAL BEAM RAIL (MODIFIED TYPE R-I) AND END ANCHORAGE TYPE I	7-24-13			
HW-910_19b	METAL BEAM RAIL (MODIFIED TYPE R-I) AND END ANCHORAGE TYPE II	7-24-13			
HW-910_19c	METAL BEAM RAIL (MODIFIED TYPE R-I) SYSTEMS 2 AND 3	7-24-13			
HW-910_20	MASH W-BEAM HARDWARE	1-05-18			
HW-910_21	METAL BEAM RAIL ( R-B MASH ) GUIDERAIL	1-25-19			
HW-910_22	METAL BEAM RAIL ( MD-B MASH) GUIDERAIL	1-05-18			
HW-910_23	METAL BEAM RAIL (R-B MASH) HALF & QUARTER POST SPACING GUIDERAIL	1-05-18			
HW-910_24	METAL BEAM RAIL SPAN SECTION TYPES II AND III	1-05-18			
HW-910_25	METAL BEAM RAIL TRANSITION 350 TO MASH	1-05-18			
HW-910_26	THRIE-BEAM ATTACHMENT HARDWARE	1-09-20			
HW-910_27	THRIE-BEAM ATTACHMENT	1-09-20			
HW-911_01	R-B END ANCHORAGE TYPE I AND II	1-25-19			
HW-911_02	MD-B END ANCHORAGE TYPE I	1-05-18			
HW-911_03	ANCHOR IN EARTH CUT SLOPE & ANCHOR IN ROCK CUT SLOPE	10-18-10			
HW-911_05	MERRITT PARKWAY GUIDERAIL END ANCHORS	7-24-13			
HW-913_01a	CHAIN LINK FENCE	5-06-19			
HW-913_01b	CHAIN LINK FENCE HARDWARE	5-06-19			
HW-913_02	CHAIN LINK FENCE GATES	5-06-19			
HW-918_01a	THREE CABLE GUIDERAIL (I-BEAM POSTS) SHEET 1	7-24-13			
HW-918_01b	THREE CABLE GUIDERAIL (I-BEAM POSTS) SHEET 2	1-26-12			
HW-918_01c	THREE CABLE GUIDERAIL (I-BEAM POSTS) SHEET 3	7-24-13			

DEPARTMENT


OF
TRANSPORTATION

OFFICE OF ENGINEERING 2800 BERLIN TURNPIKE NEWINGTON, CT 06111


NOT TO SCALE

#### **GENERAL NOTES:**


1. ALL DIMENSIONS ARE SUBJECT TO MANUFACTURING TOLERANCES.



**DETAIL "A"** 



DIAMOND PATTERN PLAN




**PLAN** 

MANHOLE FRAME AND COVER


CTDOT STORM

CTDOT


MM DD X



MANHOLE FRAME AND COVER



MANHOLE COVER WITH DIAMOND PATTERN



SEE DETAIL "A"—

MANHOLE COVER PLAN

NOT TO SCALE

SIGNATURE BLOCK:

OFFICE OF ENGINEERING 2800 BERLIN TURNPIKE NEWINGTON, CT 06111 SUBMITTED BY:

Leo Fontaine, P.E. 2020.07.08 09:26:08-04'00'

APPROVED BY:

Digitally signed by James Fallon, P.E.
ON: E-James Fallon, P.E.
ON: E-James Fallon, P.E.
ON: B-James Fallon, P.E.
ON: James Fallon, P.E.

STATE OF CONNECTICUT

DEPARTMENT

OF

TRANSPORTATION

CUT

CONNECTION

C

CTDOT STANDARD SHEET STANDARD SHEET TITLE:

MANHOLE FRAME AND COVER

STANDARD SHEET NO..

HW-586\_10a

#### **GENERAL NOTES:** 1. ALL DIMENSIONS ARE SUBJECT TO MANUFACTURERS TOLERANCE. 3" MIN. EMBEDMENT-2. SEE SHEET NO. HW-586\_10a, OR HW-586\_10b FOR MANHOLE FRAME, COPOLYMER POLYPROPYLENE GRATE AND COVER DETAIL. PLASTIC STEP WITH METAL CORE 10" MIN.-16" MAX. -4" MIN.-6" MAX. WALL THICKNESS-STEP DETAIL FRAME AND COVER FRAME AND COVER ADJUST TO GRADE WITH MAX. OF FOUR COURSES OF BRICK OR (SEE NOTE 2) (SEE NOTE 2) ADJUST TO GRADE WITH MAX. OF FOUR COURSES OF BRICK OR FRAME AND COVER (SEE NOTE 2) GRADE RINGS ADJUST TO GRADE WITH MAX. OF FOUR COURSES OF BRICK OR -GRADE RINGS FRAME AND COVER— (SEE NOTE 2) -GRADE RINGS –5" WALL 5" WALL--REINFORCEMENT -REINFORCEMENT -REINFORCEMENT 30" MIN, 4' DIA. FLAT TOP FLAT TOP 4' DIA.-3' PRECAST REINFORCED CONCRETE MANHOLE ECCENTRIC CONE 36" MIN. -WELDED WIRE 36" DIA. OPENING WELDED WIRE 36" DIA. OPENING 36" DIA. OPENING 2' TRANSITION 8" MIN. FABRIC **FABRIC** OPENING **HEIGHT** 12" MIN -16" MAX 6' DIA. −7" WALL 7" WALL -5" WALL - 4' DIA. - 5" WALL -<del>- |-</del> 6" WALL 6" WALL - 5' DIA.-<del>-</del> - 6" WALL -6' DIA.-−5' DIA.-6" WALL + FLAT SLAB TOP FOR RISER FLAT SLAB TOP FOR RISER FLAT SLAB TOP **TRANSITION REDUCER** FOR RISER **ECCENTRIC CONE SECTION SECTION SECTION SECTION SECTION SECTION** -6' DIA<del>.</del>

- REINFORCEMENT

FLAT TOP

